

ContecTile 80

Cementitious Tile Adhesive

Description:

ContecTile 80 is a tile adhesive for general purpose supplied in powder form, only the addition of water and proper mixing is needed to acquire putty like mix ready to be used. ContecTile 80 is available in white and grey colors.

Uses:

ContecTile 80 is a cementitious tile adhesive that forms a high bond between tiles, marble and concrete or plaster on vertical and horizontal surfaces. Suitable for various types of tiles: ceramic, porcelain, mosaics, and cement tiles.

Advantages:

- Used internally and externally.
- Thin layer, easy to achieve evenness of tiles.
- Excellent bond strength.
- Can be used on gypsum, cement board.
- Economical.

Standards:

- Complies with the requirements of BS 12004, ISO 13007-1 as a normal cementitious tile adhesive (C1).

Application:

Substrate should be clean, sound, and free from oil, grease, rust and other impurities. Absorbent substrates must be wetted to saturated surface dry (SSD) conditions.

Mix 5 to 6 liters of water with 20 kg powder of ContecTile 80 with a slow speed drill until a homogeneous, lump free consistency is achieved.

Apply ContecTile 80 onto the substrate at about 3 mm and then overrun a gain with a notched spatula. Place tile firmly onto adhesive with a twisting motion and level by tapping as required. Always make sure that the layer of spread adhesive is fresh and has not formed skin. Adverse atmospheric conditions such as strong winds and direct sun may extremely reduce the workability time. Pointing of joints may be executed after 6 and 24 hours for walls and floors, respectively.

Application Temperature: 5-35C°

Ready to grout: 24 hrs

Pot life: 8 hrs

Open time: >20 min

Packaging:

ContecTile 80 is supplied in 20 kg bags.

Coverage:

Approximate 5 m² at 3mm thickness.

Special Notes:

Do not use ContecTile 80 on painted surfaces or on steel. The product should not be exposed to moving water, frost, strong winds, and direct sunlight during application.

Shelf Life/ Storage:

Shelf life is 12 months if stored in a dry, cool and covered location.

Safety Precautions:

ContecTile 80 does not fall into the hazard classification of current regulations. However, it should not be swallowed or allowed to come into contact with eyes. Suitable protective gloves and goggles should be worn.

Splashes on the skin should be removed with water. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If swallowed seek medical attention immediately – do not induce vomiting.

08/2022-CTC revised 02/2024